

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (Original) A catheter having a torque transmitting shaft, comprising:
an elongate shaft having an outer surface; and
a raised pattern disposed on the outer surface, wherein the raised pattern defines means for improving the transmission of torque along the elongate shaft when torqued.
2. (Original) The catheter in accordance with claim 1, wherein the raised pattern comprises a plurality of diamond shapes spaced by channels therebetween.
3. (Original) The catheter in accordance with claim 1, wherein means for improving the transmission of torque comprises a plurality of bearing points.
4. (Original) The catheter in accordance with claim 3, wherein the bearing points contact one another when the elongate shaft is torqued.
5. (Original) A catheter having a torque transmitting shaft, comprising:
an elongate shaft having a proximal end, a distal end, a lumen extending therethrough, a core member having a proximal end and distal end, an inner surface, and an outer surface, wherein the inner surface is in fluid communication with the lumen; and
a raised pattern disposed on the outer surface, the raised pattern further comprising a plurality of bearing points, wherein the raised pattern improves the transmission of torque along the elongate shaft by contact between the bearing parts.
6. (Original) The catheter in accordance with claim 5, wherein the raised pattern is formed by laser ablation.
7. (Original) The catheter in accordance with claim 5, wherein the raised pattern is formed by overmolding.

8. (Original) The catheter in accordance with claim 5, wherein the raised pattern is formed by hot die casting.

9. (Original) The catheter in accordance with claim 5, wherein the raised pattern is formed by embossing.

10. (Original) The catheter in accordance with claim 5, wherein the raised pattern is formed by extrusion.

11. (Original) The catheter in accordance with claim 5, wherein the bearing points contact one another when the elongate shaft is torqued.

12. (Original) A method of generating torque transmittance within a catheter shaft, comprising the steps of:

providing a catheter comprising an elongate shaft having an outer surface; and
disposing a raised pattern on the outer surface, wherein the raised pattern forms means for improving the transmission of torque along the elongate shaft.

13. (Original) The method in accordance with claim 12, wherein the catheter is a guide catheter.

14. (Original) The method in accordance with claim 12, wherein the catheter is a balloon catheter.

15. (Original) The method in accordance with claim 12, wherein the raised pattern is formed by laser ablation.

16. (Original) The method in accordance with claim 12, wherein the raised pattern is formed by overmolding.

17. (Original) The method in accordance with claim 12, wherein the raised pattern is formed by hot die casting.

18. (Original) The method in accordance with claim 12, wherein the raised pattern is formed by embossing.

19. (Original) The method in accordance with claim 12, wherein the raised pattern is formed by extrusion.

20. (Original) The method in accordance with claim 12, wherein the raised pattern further comprises a plurality of bearing points.

21. (Original) The method in accordance with claim 20, wherein the bearing points contact one another when the elongate shaft is torqued.

22. (Original) The method in accordance with claim 21, wherein the bearing points transfer torque along the elongate shaft.